

Boring Designation C-303

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT Gulf County Supplemental Port St. Joseph, Florida				9. SIZE AND TYPE OF BIT 2.0 In.			
2. BORING DESIGNATION C-303				10. COORDINATE SYSTEM/DATUM Florida State Plane North		HORIZONTAL NAD 1983	VERTICAL NAVD 88
3. DRILLING AGENCY				11. MANUFACTURER'S DESIGNATION OF DRILL		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER Athena				12. TOTAL SAMPLES		DISTURBED	UNDISTURBED (UD)
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				DEG. FROM VERTICAL	BEARING		
6. THICKNESS OF OVERBURDEN 0.0 Ft.				13. TOTAL NUMBER CORE BOXES			
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				14. ELEVATION GROUND WATER			
8. TOTAL DEPTH OF BORING 12.0 Ft.				15. DATE BORING		STARTED 07-25-06	COMPLETED 07-25-06
				16. ELEVATION TOP OF BORING -35.3 Ft.			
				17. TOTAL RECOVERY FOR BORING 10.5 Ft.			
				18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist			

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-35.3	0.0					
			Fine grained quartz sand with few mud-filled burrows. Layer of coarse shell hash from 3.7' to 4'. Abrupt contact, white (10YR-8/1), (SP).		1	Sample #1, Depth = 0.5' - 0.8'
					2	Sample #2, Depth = 2.5' - 2.8'
-39.3	4.0					
			Mud. Abundant cobble-sized bivalves from 4'-5'. Muddy fine grained quartz sand-filled burrows rom 4'-5'. White fine grained sand interbedded from 7' to 8.2', very dark gray (10YR-3/1), (ML).			
-45.8	10.5					
			End of Boring			

FLORIDA DEP ROSS GULF COUNTY SUPPLEMENTAL.GPJ FL DEP ROSS.GDT 12/5/07