

| | | | | | | | |
|--|--|-----------------|--|---|----------------|--|------------------------------|
| DRILLING LOG | | DIVISION | | INSTALLATION | | SHEET 1 OF 1 SHEETS | |
| 1. PROJECT Gulf County Supplemental Port St. Joseph, Florida | | | | 9. SIZE AND TYPE OF BIT 2.0 In. | | | |
| 2. BORING DESIGNATION C-204 | | | | 10. COORDINATE SYSTEM/DATUM Florida State Plane North | | HORIZONTAL NAD 1983 | VERTICAL NAVD 88 |
| 3. DRILLING AGENCY | | | | 11. MANUFACTURER'S DESIGNATION OF DRILL | | <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER | |
| 4. NAME OF DRILLER Athena | | | | 12. TOTAL SAMPLES | | DISTURBED | UNDISTURBED (UD) |
| 5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | | | DEG. FROM VERTICAL | BEARING | | |
| 6. THICKNESS OF OVERBURDEN 0.0 Ft. | | | | 13. TOTAL NUMBER CORE BOXES | | | |
| 7. DEPTH DRILLED INTO ROCK 0.0 Ft. | | | | 14. ELEVATION GROUND WATER | | | |
| 8. TOTAL DEPTH OF BORING 10.0 Ft. | | | | 15. DATE BORING | | STARTED 07-24-06 | COMPLETED 07-24-06 |
| | | | | 16. ELEVATION TOP OF BORING -35.1 Ft. | | | |
| | | | | 17. TOTAL RECOVERY FOR BORING 8.4 Ft. | | | |
| | | | | 18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist | | | |

| ELEV. (ft) | DEPTH (ft) | LEGEND | CLASSIFICATION OF MATERIALS Depths and elevations based on measured values | % REC. | BOX OR SAMPLE | REMARKS |
|---------------|---------------|--------|---|-----------|------------------|--------------------------------|
| -35.1 | 0.0 | | | | | |
| -38.7 | 3.6 | | Fine grained quartz sand with trace coarse blackened shell fragments and cobble-sized shells. Abrupt contact, white (10YR-8/1), (SP). | | 1 | Sample #1, Depth = 1.0' - 1.3' |
| -41.8 | 6.7 | | Mud with few muddy sand-filled burrows. Abrupt contact, dark gray (10YR-4/1), (ML). | | | |
| -43.5 | 8.4 | | Fine grained quartz sand with some mud-filled burrows and mud layers at base, white (10YR-8/1), (SP). | | | |
| | | | End of Boring | | | |