

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
1. PROJECT Gulf County Supplemental Port St. Joseph, Florida				9. SIZE AND TYPE OF BIT 2.0 In.			
				10. COORDINATE SYSTEM/DATUM Florida State Plane North		HORIZONTAL NAD 1983	
2. BORING DESIGNATION C-405		LOCATION COORDINATES X = 1,679,655.47 Y = 253,623.2		11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER			
3. DRILLING AGENCY			CONTRACTOR FILE NO.		12. TOTAL SAMPLES		DISTURBED UNDISTURBED (UD)
4. NAME OF DRILLER Athena				13. TOTAL NUMBER CORE BOXES			
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL		BEARING		14. ELEVATION GROUND WATER	
6. THICKNESS OF OVERBURDEN 0.0 Ft.				15. DATE BORING		STARTED 07-25-06	COMPLETED 07-25-06
7. DEPTH DRILLED INTO ROCK 0.0 Ft.				16. ELEVATION TOP OF BORING -35.9 Ft.			
8. TOTAL DEPTH OF BORING 12.0 Ft.				17. TOTAL RECOVERY FOR BORING 11.6 Ft.			
				18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist			

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-35.9	0.0					
			Fine grained quartz sand with few mud-filled burrows. Abrupt contact, white (10YR-8/1), (SP).		1	Sample #1, Depth = 0.5' - 0.8'
					2	Sample #2, Depth = 3.0' - 3.3'
-40.3	4.4					
			Very muddy fine grained quartz sand. Decreasing fines with depth. Abundant fine grained quartz sand-filled burrows from 6' to base, dark gray (10YR-4/1), (SM).			
-47.5	11.6					
			End of Boring			