

<b>DRILLING LOG</b>		<b>DIVISION</b>		<b>INSTALLATION</b>		<b>SHEET 1 OF 1 SHEETS</b>	
<b>1. PROJECT</b> Gulf County Supplemental Port St. Joseph, Florida				<b>9. SIZE AND TYPE OF BIT</b> 2.0 In.			
<b>2. BORING DESIGNATION</b> C-404				<b>10. COORDINATE SYSTEM/DATUM</b> Florida State Plane North		<b>HORIZONTAL</b> NAD 1983	<b>VERTICAL</b> NAVD 88
<b>3. DRILLING AGENCY</b>				<b>11. MANUFACTURER'S DESIGNATION OF DRILL</b>		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
<b>4. NAME OF DRILLER</b> Athena				<b>12. TOTAL SAMPLES</b>		<b>DISTURBED</b>	<b>UNDISTURBED (UD)</b>
<b>5. DIRECTION OF BORING</b> <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				<b>13. TOTAL NUMBER CORE BOXES</b>		<b>14. ELEVATION GROUND WATER</b>	
<b>6. THICKNESS OF OVERBURDEN</b> 0.0 Ft.				<b>15. DATE BORING</b>		<b>STARTED</b> 07-25-06	<b>COMPLETED</b> 07-25-06
<b>7. DEPTH DRILLED INTO ROCK</b> 0.0 Ft.				<b>16. ELEVATION TOP OF BORING</b> -37.2 Ft.		<b>17. TOTAL RECOVERY FOR BORING</b> 11.2 Ft.	
<b>8. TOTAL DEPTH OF BORING</b> 12.0 Ft.				<b>18. SIGNATURE AND TITLE OF INSPECTOR</b> LA Coastal Geologist			

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-37.2	0.0					
-39.1	1.9		Fine grained quartz sand with trace mud-filled burrows. Abrupt contact, white (10YR-8/1), (SP).			
-47.2	10.0		Muddy fine grained quartz sand with abundant coarse to gravel-sized shell fragments. Gradational contact, dark gray (10YR 4/1) to, gray (10YR-5/1), (SM).			
-48.4	11.2		Fine grained quartz sand, light gray (10YR-7/1), (SP).			
			End of Boring			

FLORIDA DEP ROSS GULF COUNTY SUPPLEMENTAL.GPJ FL DEP ROSS.GDT 12/5/07