

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Gulf County Supplemental Port St. Joseph, Florida			9. SIZE AND TYPE OF BIT 2.0 In. 10. COORDINATE SYSTEM/DATUM HORIZONTAL VERTICAL Florida State Plane North NAD 1983 NAVD 88	
2. BORING DESIGNATION C-512		LOCATION COORDINATES X = 1,681,723.68 Y = 247,841.63		
3. DRILLING AGENCY		CONTRACTOR FILE NO.		
4. NAME OF DRILLER Athena			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL BEARING		
6. THICKNESS OF OVERBURDEN 0.0 Ft.			12. TOTAL SAMPLES DISTURBED UNDISTURBED (UD)	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			13. TOTAL NUMBER CORE BOXES	
8. TOTAL DEPTH OF BORING 12.5 Ft.			14. ELEVATION GROUND WATER	
			15. DATE BORING STARTED COMPLETED 07-26-06 07-26-06	
			16. ELEVATION TOP OF BORING -32.2 Ft.	
			17. TOTAL RECOVERY FOR BORING 12.1 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR LA Coastal Geologist	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-32.2	0.0					
			Fine grained quartz sand. Mud layer from 2.8' to 3.1'. Abrupt contact, white (10YR-8/1), (SP).		1	Sample #1, Depth = 0.5' - 0.8'
-35.9	3.7				2	Sample #2, Depth = 3.2' - 3.5'
			Muddy, shelly, peaty fine grained quartz sand with some fine grained quartz sand-filled burrows. Gradational contact, dark gray (10YR-4/1), (SM).			
-39.1	6.9					
			Fine grained quartz sand with abundant mud-filled burrows and trace peat, light gray (10YR 7/1) to, gray (10YR-6/1), (SP-SM).			
-44.3	12.1					
			End of Boring			

FLORIDA DEP ROSS GULF COUNTY SUPPLEMENTAL.GPJ FL DEP ROSS.GDT 12/5/07