

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Jacksonville District			SHEET 1 OF 1 SHEETS		
1. PROJECT Sarasota County, FL BEC Borrow Area 8O				9. SIZE AND TYPE OF BIT See Remarks					
2. BORING DESIGNATION VB-SASP06-8O-19		LOCATION COORDINATES X = 493,615 Y = 951,648		10. COORDINATE SYSTEM/DATUM State Plane, FLE (U.S. Ft.)		HORIZONTAL NAD83	VERTICAL NAVD88		
3. DRILLING AGENCY Corps of Engineers - CESAW		CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Alpine 270 Vibracore on D/B Snell		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER			
4. NAME OF DRILLER L. Gaughf				12. TOTAL SAMPLES		DISTURBED 0	UNDISTURBED (UD) 0		
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL		BEARING		13. TOTAL NUMBER CORE BOXES 0			
6. THICKNESS OF OVERBURDEN N/A				14. ELEVATION GROUND WATER N/A		15. DATE BORING STARTED 06-26-06 COMPLETED 06-26-06			
7. DEPTH DRILLED INTO ROCK N/A				16. ELEVATION TOP OF BORING -44.0 Ft.		17. TOTAL RECOVERY FOR BORING 100 %			
8. TOTAL DEPTH OF BORING 3.0 Ft.				18. SIGNATURE AND TITLE OF INSPECTOR Assem Elsayed, Geotechnical Engineer					
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/1 FT.	N-VALUE
-44.0	0.0						-44.0		
-44.2	0.3		SAND, poorly-graded, mostly fine to coarse-grained sand-sized shell, little fine to coarse-grained sand-sized quartz, moist, 2.5Y 5/1 gray (SP)	100			-44.3 Vibracore		
			SAND, silty, mostly fine to coarse-grained sand-sized quartz, little silt, moist, 2.5Y 5/1 gray (SM)	100			Vibracore		
-47.0	3.0						-47.0		
			NOTES: 1. USACE Jacksonville is the custodian for these original files. 2. Soils are field visually classified in accordance with the Unified Soils Classification System. 3. Elevation based on predicted tide						