

DRILLING LOG		DIVISION South Atlantic		INSTALLATION Jacksonville District			SHEET 1 OF 2 SHEETS		
1. PROJECT Vibracore Borings Offshore Sarasota BEC				9. SIZE AND TYPE OF BIT 3.5" Vibracore					
2. BORING DESIGNATION VB-SCV10-71		LOCATION COORDINATES X = 491,059 Y = 938,071		10. COORDINATE SYSTEM/DATUM State Plane, FLW (U.S. Ft.)		HORIZONTAL NAD83		VERTICAL NAVD88	
3. DRILLING AGENCY Corps of Engineers - CESAJ		CONTRACTOR FILE NO.		11. MANUFACTURER'S DESIGNATION OF DRILL Vibracore		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER			
4. NAME OF DRILLER American Vibracore Services, Inc.				12. TOTAL SAMPLES		DISTURBED 3		UNDISTURBED (UD) 0	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL		BEARING		13. TOTAL NUMBER CORE BOXES 0			
6. THICKNESS OF OVERBURDEN N/A				14. ELEVATION GROUND WATER					
7. DEPTH DRILLED INTO ROCK N/A				15. DATE BORING		STARTED 07-23-10		COMPLETED 07-23-10	
8. TOTAL DEPTH OF BORING 11.0 Ft.				16. ELEVATION TOP OF BORING -45.2 Ft.					
				17. TOTAL RECOVERY FOR BORING 100 %					
				18. SIGNATURE AND TITLE OF INSPECTOR Daniel G. Blaydes, Geotechnical Engineer					
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS	% REC.	BOX OR SAMPLE	RQD OR UD	REMARKS	BLOWS/1 FT.	N-VALUE
-45.2	0.0		SAND, poorly-graded, mostly fine to medium-grained sand-sized quartz, some medium to coarse-grained sand-sized shell, 10YR 5/1 gray (SP)	100			-45.2		
					1		-47.2		
				100			Vibracore		
					2		-49.2		
-50.1	4.9		At El. -49.2 Ft., mostly fine-grained sand-sized quartz, little medium-grained sand-sized shell, 10YR 6/1 gray	100			Vibracore		
			SAND, silty, mostly fine-grained sand-sized quartz, little silt, few medium-grained sand-sized shell, 10YR 7/1 light gray (SM)		3		-51.2		
				100			Vibracore		
-56.2	11.0		At El. -54.4 Ft., 10YR 4/1 dark gray				-56.2		
			NOTES: 1. Soils are field visually classified in accordance with the Unified Soils Classification System. 2. Laboratory Testing Results						
			SAMPLE ID	SAMPLE DEPTH	LABORATORY CLASSIFICATION				
			1	2.0/2.5	SP*				

DRILLING LOG (Cont. Sheet)			INSTALLATION Jacksonville District				SHEET 2 OF 2 SHEETS			
PROJECT Vibracore Borings Offshore Sarasota BEC			COORDINATE SYSTEM/DATUM State Plane, FLW (U.S. Ft.)		HORIZONTAL NAD83	VERTICAL NAVD88				
LOCATION COORDINATES X = 491,059 Y = 938,071			ELEVATION TOP OF BORING -45.2 Ft.							
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS		% REC.	BOX OR SAMPLE	ROD OR UD	REMARKS	BLOWS/ 1 FT.	N-VALUE
			2	4.0/4.5	SP*					
			3	6.0/6.5	SM*					
			*Lab visual classification based on gradation curve. No Atterberg limits.							